

## MOLEX - MPM DIN FORM B INDUSTRIAL / DIN FORM B

C22200N0R

Form Industrial, 2P+Earth, Ext Thread, NBR Gask, IP67, Black

- With or without LED and transient protection
- Fibreglass-reinforced housing
- Turnable insert
- 11 mm or 10 mm connector distance EN175301-803 (DIN43650-B Industrial/-B)



### PRODUCT DESCRIPTION

IP67 rated DIN valve connectors with improved strain relief. Cable retention force increased by up to 20% over internal nut styles. Enlarged Cable range that covers the PG9 and PG11 internal thread connector cable range. Conforms to EN 175301-803.

### TECHNICAL DATA

Cable diameter max	9 mm
Cable diameter min	4 mm
Circuit	No circuit
Colour LED	No LED
Cross section max	1,5 mm <sup>2</sup>
Current max	16 A
Housing Colour	Black
Housing material	Polyamide
IP class	IP67
LED indicator	No
Manufacturer part no.	1212020001
Material packing	NBR
Number of poles	2 + earth
Rated voltage	250 V AC/300 V DC

**Screw and gasket**

Integrated NBR Gasket &amp; IP67 screw

**Temperature operational max**

90 °C

**Temperature operational min**

-40 °C

