

## HONSBERG - UK & UKV SERIES FLOW INDICATOR

Flow display with float

UK-020GML0000

Flow meter 1/8", 0,04-0,5 NI/min,air

- For liquids and air up to 6 bar
- Flow from 0.04 to 100 NI/min. air (0.2 to 220 l/h water)
- With or without needle valve



### PRODUCT DESCRIPTION

Model UK is a variable area type flow meter. It is available in two different versions, with or without needle valve. It has been developed to measure liquids and gases in various forms.

### SPECIAL VERSIONS

- Special scales
- Connections in stainless steel
- Connections upwards and downwards (PVC)

### TECHNICAL DATA

|                                 |                                 |
|---------------------------------|---------------------------------|
| <b>Accuracy</b>                 | ± 5% of full setpoint           |
| <b>Connection type</b>          | Internal thread, NPT 1/8 "      |
| <b>Flow range max</b>           | 0,5 NI/min                      |
| <b>Flow range min</b>           | 0,04 NI/min                     |
| <b>Function</b>                 | Flow indicator, float body      |
| <b>Material of body</b>         | Acrylic                         |
| <b>Material of connection</b>   | Brass                           |
| <b>Material of seals</b>        | NBR                             |
| <b>Material suspension body</b> | Glass                           |
| <b>Pressure drop</b>            | Approx. 0.1 bar at maximum flow |
| <b>Pressure range max</b>       | 6 bar                           |

|                         |           |
|-------------------------|-----------|
| Temperature of media to | 65 °C     |
| Type of flow component  | Flowmeter |
| Weight                  | 0,13 kg   |

