

## RK SAFE BOX TS35/100

17690.4

RK-Safe-Box TS 35/100 BK

- Securable cover to prevent access
- Designed for use on CT Link assemblies
- Compatible with PTK disconnect range



### PRODUCT DESCRIPTION

Using their innovative terminal block housing, RK Safe-Box, Contaclip offer you a quick and easy protection for terminal blocks, electronic transformers etc., which are installed on mounting rails. The Safe-Box effectively prevents the unauthorised operation of converter terminals or the changing of the wiring particularly in the pre-meter area of power distribution systems. The side panels are directly on the mounting plate and totally enclose the components or assemblies which are to be protected. The wire-feed through the walls of the box simplifies the wiring and makes the subsequent manipulation of the clamp connections with a closed box impossible. Without the transparent lid, the internal dimensions of the box can be extended by 16 mm using the built-in sliding mechanism. This makes maintenance work or the exchange of terminals or components much easier.

#### Features:

- Quick and easy to install on TS 35 DIN mounting rails
- Highest mechanical attachment to the mounting rail
- When fitted, it cannot be unlocked from the mounting rail, nor can it be pulled off
- Three seal fitting locations are available
- Transparent lid
- Any alterations are immediately detectable
- The sliding mechanism of the two housing halves means that the installed components are more easily accessible during maintenance.

## TECHNICAL DATA

### GENERAL DATA

|        |       |
|--------|-------|
| Colour | Black |
|--------|-------|

### DIMENSIONS

|                  |          |
|------------------|----------|
| Length           | 91 mm    |
| Width            | 101,3 mm |
| Height TS 35/7.5 | 68,5 mm  |
| Height TS 15/5.5 | 76 mm    |
| IP class         | IP20     |

## MATERIALS

|                                   |               |
|-----------------------------------|---------------|
| <b>Material</b>                   | Polyamide 6.6 |
| <b>Flammability class</b>         | UL94-V0       |
| <b>Operating temperature from</b> | -40 °C        |
| <b>Operating temperature to</b>   | 120 °C        |

## ADDITIONAL DATA

|                          |          |
|--------------------------|----------|
| <b>Tariff code</b>       | 85369010 |
| <b>Country of origin</b> | DE       |
| <b>Weight</b>            | 77 g     |
| <b>Pack size</b>         | 1        |