

EXTERNAL LINK CROSS CONNECTORS

AQI External Links

2032.0

AQI 2/5/11 - 2 pole External Cross connector for SRK2.5/RKD2.5/IK2.5/IKD2.5/BKA2.5

- Insulated for protection
- Reliable & secure fixing



PRODUCT DESCRIPTION

External cross connection links makes it possible to connect potentials of terminals where there is no option of a central cross connection channel.

These links are quicker, easier and a more reliable way of linking than using wire links with ferrules.

When using the external, the rated cross section of wire is reduced to the next smallest size.

TECHNICAL DATA

GENERAL DATA

Colour	Yellow
Mounting	Push in
Contamination degree	3
Rated current IEC	27 A
Additional information	für SRK 2,5(1.Gen.) RKD 2,5 IK 2,5 IKD 2,5 BKA 2,5

DIMENSIONS

Width	9,26 mm
Pitch	5 mm

CONNECTION DATA

Number of poles	2
-----------------	---

MATERIALS

Flammability class	UL94-V2
Operating temperature from	-40 °C

Material	Copper
Operating temperature to	105 °C
Insulation material	Polyamide 6.6

ADDITIONAL DATA

Pack size	50
Country of origin	DE
Tariff code	85369010
Weight	0,56 g