

0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

DIN RAIL & BRACKETS

TS, TST, TWST

TS35/7.5-CAP Protective Cap for TS35 x 7.5mm Din Rail *ZCONTACLIP*

• Angled mounting brackets • TS35, TS15 & G-rail

- · Galvanised, passivated steel or aluminium versions
- Slotted or solid
- Custom sizes

PRODUCT DESCRIPTION

The Conta-Clip din rail conforms to the European Standard EN 60715 and are available with various slot sizes or as solid rail.

Most or the range are available in galvanised steel or with the zinc/chromate plating. Aluminium rails can be offered but are subject to minimum order quantities. We also offer protective caps to reduce the need for deburring and protection against the sharp-edged ends on the rail

A selection of galvanised passivated steel angled brackets is also available to stand of the rail from the back plates. These have either M5 or M6 threaded hole as standard.

OEM can offer Custom pre-cut sizes to suit your application and reduce assembly time. Please contact panel@oem.co.uk for pricing on pre-cut rail or fully assembled terminal assemblies.

TECHNICAL DATA

GENERAL DATA


Colour	Grey
DIMENSIONS	
Length	37,5 mm
Width	7 mm
Height	9 mm
MATERIALS	
Flammability class	UL94-V2
Material	Polyamide
ADDITIONAL DATA	
Pack size	100
Country of origin	DE

39269097

0,55 g







T