



## T SERIES, MODULAR BEACON, Ø75MM

859501313

LED Steady/flashing, Ø75mm, Amber, 230-240 V ac,  
TDC

- Ø75mm Modular beacon
- Steady, flashing and Multi-strobe light options
- Wide control voltage range



### PRODUCT DESCRIPTION

AUER's T Series range begins with a Ø 75 mm large comprehensive modular beacon range, the design is modern, efficient with long-life LED beacons in functions. Settings include LED steady/flashing which are both externally addressable and LED multi strobe, both strobe patterns, which are 6 times fast strobe and multi strobe, are again externally addressable.

Also including a steady beacon option with BA15d socket for 7 W incandescent bulb, the T Series can be used for a range of applications involving industrial and general applications. It is fit for plc applications like leakage and inrush current. And has a UL type of 4/4X/13 (excluding TNL and TMW+TVS).

There are also optionally available protective vents for pressure balance in harsh weather conditions (humidity, high temperature fluctuations, etc.) for TMW, TMF, TNL. A comprehensive range of selectable mounting options, and an Ingress protection of IP66.

## TECHNICAL DATA

### GENERAL DATA

Lens colour	Orange
Light type	Flashing, Steady
Light source	LED
Mounting	Bayonet

### RATED OPERATING CONDITIONS

Nominal Supply Voltage	230-240 V AC
Nominal current	66 mA
Flash frequency	2 Hz
Operational temperature	-30°C ... 60°C

Terminal connection

2,5 mm<sup>2</sup>

## DIMENSIONS

Height

75 mm

Diameter

75 mm

Weight

86 g

## ADDITIONAL DATA

IP class

IP66

IK class

8

