

OEM Automatic Ltd

Address: Whiteacres, Whetstone Leicester, LE8 6ZG 0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk



ACTUONIX - MINIATURE LINEAR ACTUATOR L16

L16-100-15012-S 12V, 100mm stroke, up to 200N force with limit switches



- Up to 200N force
- Up to 32mm/s speed
- From 50mm to 140mm stroke
- 12v dc with potentiometer or limit switches
- 6V RC controller options

PRODUCT DESCRIPTION

Actuonix Motion Devices' unique line of Miniature Linear Actuators enables a new generation of motion-enabled product designs, with capabilities that have never before been combined in a device of this size. These linear actuators are a superior alternative to designing your own push/pull mechanisms.

The L16 actuators are complete, self contained linear motion devices with position feedback for sophisticated position control capabilities, end of stroke limit switches for simple two position automation, or RC servo. Several gear ratios are available to give you varied speed/force configurations.

TECHNICAL DATA

Back drive force	102 N
Duty cycle	20 %
Force max	200 N
IP class	IP54
Nominal speed, no load	8 mm/s
Ratio	150:1
Sound level	60 dB
Static load max	200 N
Stroke	100 mm
Temperature operational max	50 °C
Temperature operational min	-10 °C
Voltage dc	12 V

L16-SS-GG-VV-C

Feature	Options		
SS: Stroke	50, 100, 140 (mm)		
GG: Gear reduction	35, 63, 150		
ratio (refer to load	(lower ratios are faster but push		
curves above)	less force, and vice versa)		
VV: Voltage	12 vdc or 6 vdc (-R only)		
C: Controller	P Potentiometer Feedback		
	S Limit Switches		
	R RC Linear Servo		

