

## BACO AUDIBLE WARNING BUZZERS

L22VA03L

Baco Buzzer 80dB 18-30V ac/dc

- Fixed or pulse signal
- IP69K from the front
- 80dB at a distance of 10cm
- 30,000h service life



### PRODUCT DESCRIPTION

### TECHNICAL DATA

Approvals	CE, CSA 22.2, IEC 60068-2-3, IEC 60068-2-30, IEC 60068-2-52, IEC 60068-2-6, IEC 60529, IEC 60947-1, IEC 60947-5-1, IEC 62262, UL, UL 508
Behind panel depth	37,2 mm
Climatic resistance - constant humid heat	IEC 60068-2-3
Climatic resistance - cyclic damp heat	IEC 60068-2-30
Climatic resistance - sea air	IEC 60068-2-52
Colour	Black
Electrical lifetime	30.000 h
Frequency	50/60 Hz
Height	29,7 mm
Insulation voltage	4 kV
IP class	IP20, IP66, IP69, IP69K, NEMA Type 1, NEMA Type 2, NEMA Type 3, NEMA Type 3R, NEMA Type 3S, NEMA Type 4, NEMA Type 4X, NEMA Type 12
Length	48,8 mm
Operating voltage ac/dc max	30 V
Operating voltage ac/dc min	18 V
Protection class	II
Recommended tightening torque	3 Nm
Sound level	80 dB
Storage temperature max	85 °C
Storage temperature min	-40 °C

Temperature operational max 70 °C

Temperature operational min -25 °C

Weight 0,02 g

