



## ASCO - 2/2 SEAT VALVE AIR CONTROLLED 1/2"-2"

E298A001

Pressure op. valve 2/2 NC 1/2" SS

- Normally closed, normally open
- Working pressure 0 to 40 bar
- For temperatures up to +250 °C
- For viscosity up to 5,000 cSt



### PRODUCT DESCRIPTION

### TECHNICAL DATA

#### GENERAL DATA

Connection	1/2 BSP
------------	---------

#### MATERIAL DATA

Material body	Stainless steel 316L
Material of seals	Graphite

#### TEMPERATURE DATA

Temperature of media from	-10 °C
Temperature of media to	250 °C

#### ADDITIONAL DATA

Viscosity max	5000 cSt
Weight	1,82 kg
Differential oil pressure max	40 bar
Function 2	Normally Closed
Differential air pressure max	40 bar

Connection air	1/8 BSP
Differential water pressure max	40 bar
Differential pressure min	0 bar
Material packing	Stainless steel
Temperature operational max	180 °C
Material box stuffing	PTFE flask filled
Function 1	2/2
Type of valve	Seat valve
Temperature operational min	-25 °C
Differential pressure max	40 bar
Material piston rod	Stainless steel
Throughput	15 mm
Material piston seal	Bronze, PTFE
Pilot pressure max	10 bar
Material controls	Nickel plated aluminum
Differential steam pressure max	40 bar

