



## ASCO - 2/2 PULSE VALVE 3/4"-3"

SCG353A043

Solenoid pulse valve 2/2 NC 3/4" 230VAC Thread



- Currentless closed
- Thread or quick coupling
- Electric/air controlled
- Housing in aluminium



### PRODUCT DESCRIPTION

### TECHNICAL DATA

#### GENERAL DATA

Connection	3/4 BSP
Flow factor / flow coefficient	14
IP class	IP65

#### MATERIAL DATA

Material body	Aluminium
Material of seals	NBR

#### TEMPERATURE DATA

Temperature of media from	-20 °C
Temperature of media to	85 °C

#### ADDITIONAL DATA

Pressure max	10 bar
Weight	0,7 kg
Material membrane	TPE

<b>Function 2</b>	Normally Closed
<b>Differential air pressure max</b>	8,5 bar
<b>Material short-circuit ring</b>	Copper
<b>Differential pressure min</b>	0,35 bar
<b>Temperature operational max</b>	85 °C
<b>Material spring</b>	Stainless steel
<b>Material plunger</b>	Stainless steel
<b>Material plunger tube</b>	Stainless steel
<b>Power consumption</b>	6 W
<b>Function 1</b>	2/2
<b>Material coil</b>	Epoxy
<b>Flow max</b>	233 l/min
<b>Temperature operational min</b>	-20 °C
<b>Throughput</b>	25 mm
<b>Voltage AC</b>	230 V