



ASCO - 215 SERIES DIRECT OPERATED

2/2

SCE215C010
Solenoid valve 2/2 NC 3/8" 230/50

- Normally closed
- Working pressure 0 bar to 3.5 bar
- Housing in aluminium



PRODUCT DESCRIPTION

TECHNICAL DATA

GENERAL DATA

Connection	3/8 BSP
Flow factor / flow coefficient	2,9
IP class	IP65

MATERIAL DATA

Material body	Aluminium
Material of seals	NBR
Material seat	Aluminium

TEMPERATURE DATA

Temperature of media from	-20 °C
Temperature of media to	85 °C

ADDITIONAL DATA

Weight	0,6 kg
Function 2	Normally Closed

Material glide ring	PTFE
Differential air pressure max	3,5 bar
Material short-circuit ring	Copper
Differential pressure min	0 bar
Temperature operational max	75 °C
Material spring	Stainless steel
Material plunger	Stainless steel
Material plunger tube	Stainless steel
Power consumption	10,5 W
Function 1	2/2
Material coil	Epoxy
Type of valve	Solenoid valve
Flow max	48,3 l/min
Temperature operational min	-20 °C
Differential pressure max	3,5 bar
Throughput	19 mm
Voltage AC	230 V

