



ASCO - 210 SERIES PILOT OPERATED

2/2

SCE210D009
Solenoid valve 2/2 NC 3/4 230/50

- Normally closed or normally open
- 3/8" up to 1 1/2" pipe size
- Air, inert gas, water & oil
- Housing in brass or stainless steel
- Flow rates from 2.6 up to 19.3 m³/h



PRODUCT DESCRIPTION

TECHNICAL DATA

GENERAL DATA

Connection	3/4 BSP
Flow factor / flow coefficient	4,3

MATERIAL DATA

Material body	Brass
Material of seals	NBR
Material seat	Brass

TEMPERATURE DATA

Temperature of media from	-20 °C
Temperature of media to	85 °C

ADDITIONAL DATA

Pressure max	20 bar
Close delay	15 ms
Viscosity max	65 cSt
Weight	0,8 kg

Differential oil pressure max	9 bar
Material membrane	NBR
Function 2	Normally Closed
Response time off	60 ms
Differential air pressure max	9 bar
Material short-circuit ring	Copper
Differential water pressure max	9 bar
Differential pressure min	0,35 bar
Temperature operational max	75 °C
Material spring	Stainless steel
Material plunger	Stainless steel
Material plunger tube	Stainless steel
Power consumption	6 W
Function 1	2/2
Material coil	Epoxy
Type of valve	Solenoid valve
Flow max	72 l/min
Temperature operational min	-20 °C
Differential pressure max	9 bar
Throughput	19 mm
Voltage AC	230 V

