



ASCO - 2/2 SERVO-CONTROLLED 1/4"- 3/4"

SCB223A125

Solenoid valve 2/2 NC 1/4" 230/50

- Normally closed
- For high pressure
- Standard working pressure 0.7 bar to 100 bar
- Housing in brass or stainless



PRODUCT DESCRIPTION

TECHNICAL DATA

GENERAL DATA

Connection	1/4 BSP
Flow factor / flow coefficient	1,3
IP class	IP65

MATERIAL DATA

Material body	Brass
Material of seals	NBR
Material seat	Brass

TEMPERATURE DATA

Temperature of media from	-20 °C
Temperature of media to	90 °C

ADDITIONAL DATA

Pressure max	100 bar
Close delay	15 ms
Viscosity max	65 cSt

Weight	0,7 kg
Differential oil pressure max	100 bar
Function 2	Normally Closed
Response time off	60 ms
Material glide ring	PTFE
Differential air pressure max	100 bar
Material short-circuit ring	Copper
Differential water pressure max	100 bar
Differential pressure min	0,7 bar
Temperature operational max	50 °C
Material plunger	Stainless steel
Material flask	Stainless steel
Material plunger tube	Stainless steel
Power consumption	16,7 W
Material seat seal	Urethane
Function 1	2/2
Material coil	Epoxy
Type of valve	Solenoid valve
Flow max	21,7 l/min
Temperature operational min	-20 °C
Differential pressure max	100 bar
Throughput	8 mm
Material piston seal	PTFE
Voltage AC	230 V

