



## ASCO - 2/2 STEAM VALVE 3/8"-1 1/2"

SCE222B093

Solenoid valve 2/2 NC 3/8" 230/50

- Normally closed
- Media temperature up to +150 °C
- Working pressure 0 to 3.5 bar steam
- Housing in brass



### PRODUCT DESCRIPTION

### TECHNICAL DATA

#### GENERAL DATA

Connection	3/8 BSP
Flow factor / flow coefficient	2,6
IP class	IP65

#### MATERIAL DATA

Material body	Brass
Material of seals	EPDM
Material seat	Brass

#### TEMPERATURE DATA

Temperature of media from	-20 °C
Temperature of media to	150 °C

#### ADDITIONAL DATA

Pressure max	10 bar
Close delay	15 ms
Weight	1,2 kg

<b>Function 2</b>	Normally Closed
<b>Response time off</b>	60 ms
<b>Material short-circuit ring</b>	Copper
<b>Differential pressure min</b>	0 bar
<b>Temperature operational max</b>	40 °C
<b>Material spring</b>	Stainless steel
<b>Material plunger</b>	Stainless steel
<b>Material plunger tube</b>	Stainless steel
<b>Power consumption</b>	10,5 W
<b>Function 1</b>	2/2
<b>Material coil</b>	Epoxy
<b>Type of valve</b>	Solenoid valve
<b>Flow max</b>	43,3 l/min
<b>Temperature operational min</b>	-20 °C
<b>Throughput</b>	16 mm
<b>Voltage AC</b>	230 V
<b>Differential steam pressure max</b>	3,5 bar

