



ASCO - 2/2 STEAM VALVE 3/8"-2"

SCE220A019

Solenoid valve 2/2 NC 3/8" 230/50

- Normally closed
- Media temperature up to +185 °C
- Working pressure 0.35 to 10 bar steam
- Housing in brass



PRODUCT DESCRIPTION

TECHNICAL DATA

GENERAL DATA

| | |
|------------|---------|
| Connection | 3/8 BSP |
| IP class | IP65 |

MATERIAL DATA

| | |
|-------------------|-------|
| Material body | Brass |
| Material of seals | EPDM |
| Material seat | Brass |

TEMPERATURE DATA

| | |
|---------------------------|--------|
| Temperature of media from | -20 °C |
| Temperature of media to | 184 °C |

ADDITIONAL DATA

| | |
|--------------|-----------------|
| Pressure max | 10 bar |
| Close delay | 40 ms |
| Function 2 | Normally Closed |

| | |
|--|-----------------|
| Response time off | 120 ms |
| Differential air pressure max | 10 bar |
| Material short-circuit ring | Copper |
| Differential water pressure max | 10 bar |
| Differential pressure min | 0,35 bar |
| Temperature operational max | 40 °C |
| Material spring | Stainless steel |
| Material plunger | Stainless steel |
| Material plunger tube | Stainless steel |
| Power consumption | 10,5 W |
| Material seat seal | PTFE |
| Function 1 | 2/2 |
| Material coil | Epoxy |
| Type of valve | Solenoid valve |
| Flow max | 43 l/min |
| Temperature operational min | -20 °C |
| Differential pressure max | 10 bar |
| Throughput | 16 mm |
| Voltage AC | 230 V |

