



ASCO - 2/2 STEAM VALVE 3/8"-2"

SCE220027

Solenoid valve 2/2 NC 1 1/4" 230VAC

- Normally closed
- Media temperature up to +185 °C
- Working pressure 0.35 to 10 bar steam
- Housing in brass



PRODUCT DESCRIPTION

TECHNICAL DATA

GENERAL DATA

Connection	1 1/4 BSP
IP class	IP65

MATERIAL DATA

Material body	Brass
Material of seals	EPDM
Material seat	Brass

TEMPERATURE DATA

Temperature of media from	-20 °C
Temperature of media to	184 °C

ADDITIONAL DATA

Pressure max	10 bar
Close delay	40 ms
Function 2	Normally Closed

Response time off	120 ms
Differential air pressure max	10 bar
Material short-circuit ring	Copper
Differential water pressure max	10 bar
Differential pressure min	0,35 bar
Temperature operational max	40 °C
Material spring	Stainless steel
Material plunger	Stainless steel
Material plunger tube	Stainless steel
Power consumption	10,5 W
Material seat seal	PTFE
Function 1	2/2
Material coil	Epoxy
Type of valve	Solenoid valve
Flow max	213 l/min
Temperature operational min	-20 °C
Differential pressure max	10 bar
Throughput	28 mm
Voltage AC	230 V

