



ASCO - 2/2 PROPORTIONAL VALVE 3/8"

SCE202A023VS3

Proportional valve 2/2 NC 3/8" 24VDC



- Normally closed
- Large flow
- Working pressure 0 to 4 bar
- Housing in brass or stainless



PRODUCT DESCRIPTION

TECHNICAL DATA

GENERAL DATA

Connection	3/8 BSP
Flow factor / flow coefficient	0,24
IP class	IP65

MATERIAL DATA

Material body	Brass
Material of seals	FPM
Material seat	Brass

TEMPERATURE DATA

Temperature of media from	-10 °C
Temperature of media to	90 °C

ADDITIONAL DATA

Pressure max	35 bar
Viscosity max	21 cSt
Weight	0,5 kg

Function 2	Normally Closed
Material glide ring	PTFE
Differential air pressure max	4 bar
Differential pressure min	0 bar
Temperature operational max	75 °C
Material spring	Stainless steel
Material plunger	Stainless steel
Material plunger tube	Stainless steel
Power consumption	8 W
Function 1	2/2
Material coil	Epoxy
Flow max	4 l/min
Temperature operational min	-10 °C
Differential pressure vacuum max	1 bar
Sensitivity	<2%
Throughput	3,2 mm
Voltage dc	24 V

