



ASCO - 2/2 PROPORTIONAL VALVE 3/8"-1/2"

SCG203B001S3
Proportional valve 2/2 NC 3/8" 24VDC

- Normally closed
- Large flow
- Working pressure 0.3 to 10 bar
- Housing in brass



PRODUCT DESCRIPTION

TECHNICAL DATA

GENERAL DATA

Connection	3/8 BSP
Flow factor / flow coefficient	2,1
IP class	IP65

MATERIAL DATA

Material body	Brass
---------------	-------

TEMPERATURE DATA

Temperature of media from	-10 °C
Temperature of media to	90 °C

ADDITIONAL DATA

Pressure max	15 bar
Viscosity max	40 cSt
Weight	0,65 kg
Material membrane	NBR

Function 2	Normally Closed
Material glide ring	PTFE
Differential pressure min	0,3 bar
Temperature operational max	75 °C
Material spring	Stainless steel
Material plunger	Stainless steel
Material plunger tube	Stainless steel
Power consumption	8 W
Material seat seal	FPM
Function 1	2/2
Material coil	Epoxy
Flow max	35 l/min
Temperature operational min	-20 °C
Differential pressure max	10 bar
Sensitivity	<2 %
Throughput	12,5 mm
Voltage dc	24 V

