



BANICO AUTOMATIC GAS VALVE ZEVF SERIES

ZEVF65

ZEVF, 2 1/2" Flanged PN16, 360, 2-way, Normally Closed



- Max pressure to 360 mbar
- Suitable for a variety of gases
- Two way normally closed design
- Available in sizes from 3/8" to 3" in Automatic



PRODUCT DESCRIPTION

Flanged gas solenoid valve from Banico Controls in an automatic and two way normally closed design. Used for safety and control of gas for shut-off in gas feed pipes. Suitable for various gases, including Natural Gas, Propane and LPG Gas.

TECHNICAL DATA

GENERAL DATA

| | |
|------------|------------------------|
| Function | 2-way, Normally Closed |
| Connection | 2 1/2" Flanged PN16 |
| IP class | IP54 |

MATERIAL DATA

| | |
|-------------------|--------------------|
| Material body | Die cast aluminium |
| Material of seals | NBR |

TEMPERATURE DATA

| | |
|--------------------------|--------|
| Temperature ambient from | -15 °C |
| Temperature ambient to | 60 °C |

ADDITIONAL DATA

| | |
|--------------|---------|
| Pressure max | 360 bar |
|--------------|---------|

| | |
|--|---------------------------|
| Weight | 15 kg |
| Max number of operations per minute | 20 |
| Material spring | Stainless Steel 302 |
| Material of filter | Stainless steel 303 |
| Response time | <1 second |
| Length | 310 mm |
| Power consumption | 72 W |
| Cable entry | PG11 Live, Neutral, Earth |
| Height | 343 mm |
| Voltage AC | 230 V |