



ASCO - 210 SERIES PILOT OPERATED

2/2

SCE210D001
Solenoid valve 2/2 NC 3/8" 230/50

- Normally closed or normally open
- 3/8" up to 1 1/2" pipe size
- Air, inert gas, water & oil
- Housing in brass or stainless steel
- Flow rates from 2.6 up to 19.3 m³/h



PRODUCT DESCRIPTION

TECHNICAL DATA

GENERAL DATA

| | |
|--------------------------------|---------|
| Flow factor / flow coefficient | 2,6 |
| Connection | 3/8 BSP |

MATERIAL DATA

| | |
|-------------------|-------|
| Material seat | Brass |
| Material of seals | NBR |
| Material body | Brass |

TEMPERATURE DATA

| | |
|---------------------------|--------|
| Temperature of media from | -20 °C |
| Temperature of media to | 85 °C |

ADDITIONAL DATA

| | |
|---------------|--------|
| Weight | 0,8 kg |
| Close delay | 15 ms |
| Viscosity max | 65 cSt |
| Pressure max | 20 bar |

| | |
|---------------------------------|------------------------|
| Power consumption | 6 W |
| Throughput | 16 mm |
| Type of valve | Solenoid valve |
| Response time off | 60 ms |
| Voltage AC | 230 V |
| Temperature operational min | -20 °C |
| Temperature operational max | 75 °C |
| Material coil | Epoxy |
| Differential air pressure max | 14 bar |
| Differential pressure max | 14 bar |
| Differential pressure min | 0,35 bar |
| Differential oil pressure max | 10 bar |
| Differential water pressure max | 10 bar |
| Flow max | 43 l/min |
| Function 1 | 2/2 |
| Function 2 | Normally Closed (SPST) |
| Material plunger | Stainless steel |
| Material short-circuit ring | Copper |
| Material spring | Stainless steel |
| Material membrane | NBR |

