



ASCO - 210 SERIES PILOT OPERATED

2/2

SCE210D009
Solenoid valve 2/2 NC 3/4 230/50

- Normally closed or normally open
- 3/8" up to 1 1/2" pipe size
- Air, inert gas, water & oil
- Housing in brass or stainless steel
- Flow rates from 2.6 up to 19.3 m³/h



PRODUCT DESCRIPTION

TECHNICAL DATA

GENERAL DATA

Flow factor / flow coefficient	4,3
Connection	3/4 BSP

MATERIAL DATA

Material seat	Brass
Material of seals	NBR
Material body	Brass

TEMPERATURE DATA

Temperature of media from	-20 °C
Temperature of media to	85 °C

ADDITIONAL DATA

Weight	0,8 kg
Close delay	15 ms
Viscosity max	65 cSt
Pressure max	20 bar

Power consumption	6 W
Throughput	19 mm
Type of valve	Solenoid valve
Response time off	60 ms
Voltage AC	230 V
Temperature operational min	-20 °C
Temperature operational max	75 °C
Material coil	Epoxy
Differential air pressure max	9 bar
Differential pressure max	9 bar
Differential pressure min	0,35 bar
Differential oil pressure max	9 bar
Differential water pressure max	9 bar
Flow max	72 l/min
Function 1	2/2
Function 2	Normally Closed (SPST)
Material plunger	Stainless steel
Material short-circuit ring	Copper
Material spring	Stainless steel
Material membrane	NBR

