



ASCO - 2/2 PROPORTIONAL VALVE 1/8"

SCG202A201VS3

Proportional valve 2/2 NC 1/8" 24VDC

- Normally closed
- Compact version
- Working pressure 0 to 8 bar
- Housing in brass or stainless



PRODUCT DESCRIPTION

TECHNICAL DATA

GENERAL DATA

IP class	IP65
Flow factor / flow coefficient	0,05
Connection	1/8 BSP

MATERIAL DATA

Material seat	Brass
Material body	Brass

TEMPERATURE DATA

Temperature of media from	0 °C
Temperature of media to	50 °C

ADDITIONAL DATA

Weight	0,2 kg
Viscosity max	50 cSt
Pressure max	35 bar
Power consumption	6,3 W

Throughput	1,2 mm
Sensitivity	<1%
Voltage dc	24 V
Temperature operational min	0 °C
Temperature operational max	40 °C
Material coil	Epoxy
Differential air pressure max	8 bar
Differential pressure min	0 bar
Differential oil pressure max	5 bar
Differential pressure vacuum max	1 bar
Differential water pressure max	5 bar
Flow max	0,7 l/min
Function 1	2/2
Function 2	Normally Closed (SPST)
Material plunger	Stainless steel
Material glide ring	PTFE
Material seat seal	FPM
Material spring	Stainless steel



