

## DATALOGIC - LIGHT CURTAINS SLIM

SL4-24-0150-E  
 957910340 Type 4 24mm Hand Res 150mm Prot  
 Height SLIM

- Range up to 6 m
- Slim profile 15x32 mm
- No dead zones
- Resolution 14, 24 and 34 mm
- Cascadable up to 3 units with 34 different protection heights at 30mm intervals



### PRODUCT DESCRIPTION

SLIM is a safety light curtain with a range of up to 6 metres designed to fit in the smallest spaces.

With 34 different protection heights at 30mm intervals it is one of the most flexible light curtains on the market.

This Type 4 light curtain maintains the highest safety level according to the latest safety standards EN ISO 13849-1 and EN 62061.

Datalogic's SLIM light curtain has built-in monitored reset, an input for monitoring of external contactors and two solid state safety outputs which are also electronically monitored.

This means that the SG4-Finger can work as a "standalone" unit if required and is not in need of any special control unit.

### TECHNICAL DATA

<b>Additional features</b>	EDM, reset functions
<b>Approvals</b>	CE, cULus, TÜV
<b>Cable connection receiver</b>	M12, 5-pole
<b>Cable connection transmitter</b>	M12, 5-pole
<b>Cable length max</b>	20 m
<b>Contact current max</b>	0,3 A
<b>DC</b>	98,80 %
<b>Distance max</b>	6 m
<b>Function</b>	Calibration mode, Manual/automatic restart, EDM
<b>In compliance with</b>	EMC, LVD, MD

<b>IP class</b>	IP65
<b>Material of body</b>	Aluminium
<b>MTTFd</b>	191 year(s)
<b>Number of beams</b>	8
<b>PL</b>	e (EN ISO 13849-1)
<b>Power consumption</b>	Transmitter 1,6W. Receiver 4,2 W. (without load)
<b>Protection height</b>	150 mm
<b>Range</b>	0,2-6 m
<b>Reaction time</b>	7 ms
<b>Resolution</b>	24 mm
<b>Safe outputs</b>	2 OSSD
<b>SFF</b>	98,93 %
<b>SIL</b>	3 (EN IEC 62061)
<b>Supply voltage</b>	24 V DC, stabilized
<b>Supply voltage</b>	24 V DC
<b>T1 (Life time in years)</b>	20
<b>Temperature operational max</b>	55 °C
<b>Temperature operational min</b>	-10 °C
<b>Type</b>	4
<b>Voltage tolerance</b>	±20 %

