

## MINIMOTOR XCDBS BRUSHLESS SERVOMOTORS WITH WORM GEARBOX

XCDBS 80/50-5-B3  
48 Vdc, 600rpm, 4.05nm, B3 mount

- Efficient and compact
- Saves separate cable runs
- up to 35nm rated torque
- Open Bus protocols
- Reduce machine build components



### PRODUCT DESCRIPTION

### TECHNICAL DATA

#### GENERAL DATA

Nominal speed	600 rpm
Nominal torque	4,05 Nm
Input voltage dc	48 Vdc
Digital inputs	2 pnp (24Vdc, 500kHz) , 3 pnp (24Vdc, 7kHz)
Outputs	1 NO 2A (42 Vdc)
Output power	345 W
Rated current	9.9 A
Nominal overload	150% x 60 sec
Motor control algorithm	Sinusoidal brushless with 12Bit single-turn / 20Bit multi-turn absolute encoder
Nominal output frequency carrier	4/8/12 kHz
Electronic brake output	24Vdc, max 0.5A
Ambient temperature	-10 ... +40°C

#### SAFETY FEATURES

IP class	IP65
CE approved	Yes
Over voltage protection	Yes
Under voltage protection	Yes

<b>Overheat protection</b>	Yes
<b>Memory error protection</b>	Yes
<b>Polarity reverse protection</b>	Yes
<b>Overcurrent protection</b>	Yes
<b>Communication error protection</b>	Yes
<b>Overload protection</b>	Yes

## COMMUNICATION

<b>Communication</b>	USB
<b>Ethercat</b>	Yes
<b>CanOpen</b>	Yes
<b>ProfiNET</b>	Yes
<b>Ethernet IP</b>	Yes
<b>Modbus RTU</b>	Yes
<b>PowerLink</b>	Yes
<b>Ratio</b>	5:1