


KUEBLER - INCREMENTAL PULSE TRANSDUCER, STAINLESS STEEL, SENDIX 5006/5026

SERIE 5006

- Housing diameter Ø58 mm
- stainless steel housing
- Axle seal in Viton® from DuPont ©
- Temperature range -40 to +85 ° C



PRODUCT DESCRIPTION

Sendix 5006/5026 is a robust incremental shaft sensor specially designed for industrial use outdoors or in the food industry. The shaft seal is in Viton® material from DuPont. Viton® is specially designed to cope with chemical impact. With its powerful housing, the sensor is more protected from impact and impact than previous models in the 58XX series. With the new Safety-Lock™ construction, the bearings in the angle sensor have been placed with a larger line spacing and a special locking latch that prevents stock displacement in any direction.

The sensor comes with shaft and hole shaft, in combination with several different flanges to fit where 58mm sensors have previously been sitting.

Please refer to the images below for ordering information.

Order code Shaft version	8.5006 Type	.XXXX4. a b c d	XXXX e		
a Flange 7 = clamping flange ø 58 mm [2.28"] A = synchro flange ø 58 mm [2.28"] C = square flange □ 63.5 mm [2.5"]	b Shaft (ø x L), with flat 1 = ø 6 x 10 mm [0.24 x 0.39"] 3 = ø 10 x 20 mm [0.39 x 0.79"] 8 = ø 3/8" x 7/8"	c Output circuit / power supply 2 = push-pull (7272 compatible with inverted signal) / 5 ... 30 V DC 5 = push-pull (with inverted signal) / 10 ... 30 V DC 4 = RS422 (with inverted signal) / 5 V DC	d Type of connection 4 = radial M12 connector, 8-pin	e Pulse rate 1, 5, 10, 12, 36, 100, 200, 250, 256, 360, 400, 500, 512, 600, 800, 1000, 1024, 1200, 2000, 2048, 2500, 3600, 4096, 5000 (e.g. 100 pulses => 0100)	Optional on request - other pulse rates - Ex 2/22 - seawater resistant (stainless steel V4A)
				Stainless steel V4A as standard types (deliverable as from 1 unit) V4A 8.5006.73X4.XXXX-V4A 1.4404	


Order code Hollow shaft	8.5026 Type	.XXXX2. a b c d	XXXX e		
a Flange 1 = with spring element, long C = with stator coupling, ø 63 mm	b Through hollow shaft 2 = ø 1/4" 4 = ø 3/8" 3 = ø 10 mm [0.39"] 5 = ø 12 mm [0.47"] 6 = ø 1/2" 8 = ø 15 mm [0.59"]	c Output circuit / power supply 2 = push-pull (7272 compatible, with inverted signal) / 5 ... 30 V DC 5 = push-pull (with inverted signal) / 10 ... 30 V DC 4 = RS422 (with inverted signal) / 5 V DC	d Type of connection 2 = radial M12 connector, 8-pin	e Pulse rate 1, 5, 10, 12, 36, 100, 200, 250, 256, 360, 400, 500, 512, 600, 800, 1000, 1024, 1200, 2000, 2048, 2500, 3600, 4096, 5000 (e.g. 100 pulses => 0100)	Optional on request - other pulse rates - Ex 2/22 - seawater resistant (stainless steel V4A)
				Stainless steel V4A as standard types (deliverable as from 1 unit) V4A 8.5026.18X2.XXXX-V4A 1.4404	

TECHNICAL DATA

Connection

M12

Housing diameter	58 mm
IP class	IP66, IP67
Mounting	Shoulder
Output	Push/Pull, RS422
Pulse max	5000
Sensor type	Incremental
Shaft diameter max	10 mm
Shaft diameter min	6 mm
Supply voltage dc max	30 V DC
Supply voltage dc min	5 V DC
Temperature operational max	85 °C
Temperature operational min	-40 °C
Version	Multiturn



1 M3, 5.5 dJup

1 3xM4, 6 dJup

Terminal assignment

Output channel	Type of connector	M12 connector, 6 pin
2, 4, 5	9006, 4	Signal
	9006, 2	Pin
		1 2 3 4 5 6 7 8 PH

Top view of mating side, male contact base



- PH: Encoder power supply (+V DC)
- PH: Encoder power supply (ground) (GND) (-V)
- A, X: Incremental output channel A
- B, S: Incremental output channel B
- 0, S: Reference signal
- PH: Plug connector housing shield