



## CHROME II MODULAR POWER SUPPLY 24VDC

DRC-24V030W1RZ

- Universal AC Input Range and DC Input Supported
- Mechanical dimension designs to meet DIN 43880 for building automation
- Class II, Double Isolation (No Earth connection is required)
- Low no load power consumption & meet with DOE VI
- NEC Class 2 / Limited Power Source (LPS) certified



### PRODUCT DESCRIPTION

### TECHNICAL DATA

#### INPUT DATA

Input voltage ac	100-240 V
Input voltage ac min	85 V AC
Input voltage ac max	264 V AC
Inrush current at 230 V ac typical	40 A

#### OUTPUT DATA

Output voltage	24 V DC
Output voltage min	21,6 V DC
Output voltage max	26,4 V DC
Output current	1,5 A
Power	36 W

#### EFFICIENCY / LIFETIME / MTBF

Efficiency	87,6 %
------------	--------

#### DIMENSIONS

Width	35 mm
-------	-------

<b>Height</b>	87,5 mm
<b>Depth</b>	55 mm
<b>Weight</b>	0,13 kg

## OTHER

<b>Approvals</b>	BSMI, CB, CCC, CE, UKCA, NEC Class 2, REACH, RoHS, TÜV, UL
<b>Hold time at 120 V ac, typical full load</b>	14 ms
<b>Hold time at 230 V ac, typical full load</b>	70 ms
<b>IP class</b>	IP20
<b>Clamp type</b>	Screw
<b>Material protection</b>	Plastic
<b>Supply frequency</b>	50-60 Hz
<b>Power consumption 120 V ac</b>	0,9 A
<b>Power consumption 230 V ac</b>	0,5 A
<b>Temperature min without derating</b>	-30 °C
<b>Temperature max without derating</b>	70 °C

