

24 V DC 20A UPS FOR EXTERNAL BATTERY 3.9-130 AH

UB20.241
 DC-UPS modul. 24VDC, 20A

- Load current 20 A
- Control of each individual battery
- Selectable output voltage in battery mode
- Temperature compensated charging
- Relay outputs for status



PRODUCT DESCRIPTION

The UB20.241 uninterruptible power supply controller (DC-UPS) is used in addition with a 24V power supply and batteries to bridge power failures or voltage fluctuations. This configuration can prevent expensive downtimes, long restart cycles and loss of data.

A unique feature of the UB20 series is the constant voltage in battery mode, which will not change as the batteries discharge. The buffer voltage in battery mode can be set to four different output values. Another feature is the utilization of two independent battery chargers for the two 12V-batteries in series. This feature makes matching batteries unnecessary and allows for precise battery charging, testing and optimized usage of the battery capacity to achieve the longest battery service life.

The UB20.241 includes many battery diagnostic functions that ensure a reliable operation of the entire system. Furthermore, a temperature controlled charging

extends the life of the batteries. It also includes a selectable buffer time limiter as well as ready, buffering and replace battery contacts. For safety and maintenance, an inhibit input signal is included which prevents a battery backup.

TECHNICAL DATA

INPUT DATA

Input current during charging	3,4 A
Input voltage from the unit	24 V DC
Input voltage for battery connection	22,8 V DC
Input voltage from the battery	24 V DC

OUTPUT DATA

Output voltage for battery operation	22,5
Output current during operation max	25 A
Output current for battery operation max	20 A (30 A @ 4 s)
Output voltage normal operation	24 V DC

Output current at 24 V dc	20 A
---------------------------	------

EFFICIENCY / LIFETIME / MTBF

Life span	122 000 h @ 20 A, 40 °C
Efficiency	99 %
MTBF (IEC 61709)	649 000 h @ 20 A, 40 °C

DIMENSIONS

Weight	0,7 kg
Depth	117 mm
Width	49 mm
Height	124 mm

OTHER

Charging the battery type	3 A
IP class	IP20
Ripple max	120 mV pp
Voltage level for battery connection	24 V DC
Power drop from +60 °C to + 70 °C	12 W/°C
Temperature min without derating	-40 °C
Permitted battery sizes	3,9-150 Ah
Approvals	ABS, CB, CE, CSA, CSA US, EX, GL, IECEx, UL
Temperature max without derating	60 °C
Material protection	Aluminium
Type Power Supply	DC-UPS



