

**CHROME MODULAR POWER SUPPLY  
5VDC**

5VDC, 1.5A, 7W

DRC-5V10W1AZ

- Width 18 mm
- Efficiency >78%
- NEC Class 2
- Din rail mount

**PRODUCT DESCRIPTION****TECHNICAL DATA****INPUT DATA**

Input voltage ac	100-240 V
Input voltage ac min	90 V AC
Input voltage dc max	375 V DC
Input voltage dc	125-375 V
Input voltage ac max	264 V AC
Inrush current at 230 V ac typical	30 A
Inrush current at 120 V ac typical	15 A
Input voltage dc min	125 V DC

**OUTPUT DATA**

Output voltage min	4,75 V DC
Output voltage	5 V DC
Output voltage max	5,25 V DC
Power	7,5 W
Output current	1,5 A

## EFFICIENCY / LIFETIME / MTBF

Efficiency	78 %
------------	------

## DIMENSIONS

Weight	0,06 kg
Depth	55,6 mm
Width	18 mm
Height	91 mm

## OTHER

IP class	IP20
Power consumption 120 V ac	0,3 A
Clamp type	Screw
Temperature min without derating	-25 °C
Hold time at 120 V ac, typical full load	10 ms
Hold time at 230 V ac, typical full load	60 ms
Power consumption 230 V ac	0,2 A
Supply frequency	50-60 Hz
Approvals	CB, CE, NEC Class 2, TÜV, UL
Temperature max without derating	55 °C
Material protection	Plastic

