

24 V DC UPS INTEGRATED BATTERY 5 AH

UBC10.241
 DC UPS & BATTERY 24VDC 10A

- Load current 10 A
- Only one 12 V battery
- Integrated high power battery of 5 Ah
- Relay outputs for status




PRODUCT DESCRIPTION

A DC-UPS system comprises a control unit with integrated 5 A high power battery, and a power supply with suitable power for the application. The battery is easy to replace by undoing the screw at the front. In case of a power failure, the battery is automatically connected and feeds the connected loads. The UPS requires only one (1) 12 V battery which then transforms up the battery voltage to 22.3 V dc, one does not need to match 2 batteries with each other and the output voltage does not follow the battery's discharge curve but is constant at 22.3 V. The battery capacity is utilised 100% compared with two series-connected batteries where one of the batteries will not be fully charged.

Two relay outputs indicate status; module ready (battery capacity >85%) and module active (buffer mode). The control unit tests the battery's condition in cycles, when it is time to replace the battery, a relay output is activated (replace battery). One sensor measures the temperature and optimises the final charging voltage. The buffer time can be set in different time ranges to save battery capacity, when a constant discharge is selected, the output voltage will be active until the battery reaches deep discharge and the control unit disconnects the battery.

A fault on the battery fuse drops the Ready output and a red LED lights on the control unit. The output has a current limit and shuts itself off after about 5 seconds after a short-circuit to save the battery and at the same time avoid tripping the battery fuse. With a short-circuit in buffer mode, the module will deliver approx. 20 A which helps to trip any secondary fuse. Monitoring of the battery fuse and current limitation with short-circuits gives an increased safety and a guarantee that the UPS will function after a short circuit. The input is galvanically isolated from the output side.

BACKUP TIMES



Discharge curve for 5 Ah battery

TECHNICAL DATA

INPUT DATA

Input current during charging	1,3 A
Input voltage from the unit	24 V DC
Input voltage for battery connection	22,8 V DC
Input voltage from the battery	12 V DC

OUTPUT DATA

Output voltage for battery operation	22,25
Output current during operation max	15 A
Output current for battery operation max	10 A (15 A @ 5 s)
Output voltage at buffering	22,25 V DC
Output voltage normal operation	24 V DC
Output current at 24 V dc	10 A

EFFICIENCY / LIFETIME / MTBF

Life span	137 400 h @ 10 A, 40 °C
Efficiency	97,8 %
MTBF (IEC 61709)	886 000 h @ 10 A, 40 °C

DIMENSIONS

Weight	2,85 kg
Depth	119 mm
Width	123 mm
Height	124 mm

OTHER

Charging the battery type	1,5 A
IP class	IP20
Ripple max	20 mV pp
Temperature min without derating	0 °C
Permitted battery sizes	5 Ah
Approvals	ABS, CB, CE, CSA, CSA US, EX, GL, IECEx, UL
Temperature max without derating	40 °C
Material protection	Aluminium
Type Power Supply	DC-UPS

