

**CHROME II MODULAR POWER SUPPLY
24VDC**

DRC-24V015W1RZ

- Universal AC Input Range and DC Input Supported
- Mechanical dimension designs to meet DIN 43880 for building automation
- Class II, Double Isolation (No Earth connection is required)
- Low no load power consumption & meet with DOE VI
- NEC Class 2 / Limited Power Source (LPS) certified

**PRODUCT DESCRIPTION****TECHNICAL DATA****INPUT DATA**

Input voltage ac	100-240 V
Input voltage ac min	85 V AC
Input voltage dc max	375 V DC
Input voltage dc	125-375 V
Input voltage ac max	264 V AC
Inrush current at 230 V ac typical	40 A
Input voltage dc min	125 V DC

OUTPUT DATA

Output voltage min	21,6 V DC
Output voltage	24 V DC
Output voltage max	26,4 V DC
Power	15 W
Output current	0,63 A

EFFICIENCY / LIFETIME / MTBF

Efficiency	87,5 %
-------------------	--------

DIMENSIONS

Weight	0,06 kg
Depth	55 mm
Width	18 mm
Height	87,5 mm

OTHER

IP class	IP20
Power consumption 120 V ac	0,5 A
Clamp type	Screw
Temperature min without derating	-40 °C
Hold time at 120 V ac, typical full load	18 ms
Hold time at 230 V ac, typical full load	79 ms
Power consumption 230 V ac	0,3 A
Supply frequency	50-60 Hz
Approvals	BSMI, CB, CCC, CE, NEC Class 2, REACH, RoHS, TÜV, UL
Temperature max without derating	70 °C
Material protection	Plastic

