

315-400A SWITCH DISCONNECTORS

30028

KU 3315 SV, Screw Mounted, 3-Pole, 315A



- Made of halogen-free thermoplastic with 100% recyclability
- Auxilliary contacts available
- Terminal covers and phase barriers available
- Icw 690V (1s) 13.5kA



PRODUCT DESCRIPTION

Katko 315-400A switch disconnectors are a reliable switch for demanding industrial applications. They are made of halogen free thermoplastics which are 100% recyclable.

Available with a direct handle, or seperate LKX150 handle and LVK228 shaft.
 Yellow/Red handles and shaft of different length available upon request.

Option for test position for testing auxilliary contacts while main contacts remain open. Note, only available on request.
 Auxilliary contacts available (1.V160KU or 2.V160KU), up to 8 NC / 8 NO. Terminal covers (LS400H and LS400F) and phase barriers (VS400) available.
 Note! Al-cables cannot be connected directly to switch terminals. For Al-cable connection please use a bi-metal cable connector.

TECHNICAL DATA

GENERAL DATA

Weight	2,05 kg
Rated thermal current, I _{th}	315 A
Nominal values with cable size	185
Number of poles	3
Rated insulation voltage U _i	1000 V
Terminals / Bolt size Cu	M10
Type	Screw-mounted

RATED OPERATIONAL CURRENT, I_E

Operational current - AC-21A - 500V	315 A
-------------------------------------	-------

Operational current - AC-23A - 500V	315 A
Operational current - AC-22A - 690V	315 A
Operational current - AC-21A - 690V	315 A
Operational current - AC-21A - 400/415V	315 A
Operational current - AC-23A - 690V	315 A
Operational current - AC-22A - 500V	315 A
Operational current - AC-23A - 400/415V	315 A
Operational current - AC-22A - 400/415V	315 A

RATED OPERATIONAL POWER FOR 3-PHASE (1500 R.P.M.) SQUIRREL CAGE INDUCTION MOTORS (KW)

Operational power - AC-23A - 400/415V	160 kW
Operational power - AC-23A - 500V	200 kW
Operational power - AC-23A - 690V	315 kW

RATED FUSED SHORT CIRCUIT CURRENT

Peak value	42 kA
Back-up fuse	400 A
Rated short circuit making capacity at 690V, I _{cm}	27.5 kA
Rated short time withstand current at 690V (1 s), I _{cw}	13.5 kA
R.M.S value, I _K	100 kA
Rated impulse withstand voltage U _{imp}	12 kV

RATED BREAKING CAPACITY, I_{CN}

Breaking capacity - AC-23A - 400/415V	2520 A
Breaking capacity - AC-23A - 500V	2520 A
Breaking capacity - AC-23A - 690V	2520 A

ADDITIONAL DETAILS

Country of origin	FI
Tariff code	85365080
Max terminal torque	40-44 Nm
Electrical endurance	2000 operations
Mechanical endurance	10000 operations

