

STAINLESS STEEL ENCLOSURES

44285

KER 316 RA2, Stainless Steel Enclosure, 3-Pole, 16A

- 16-1600A switch ratings
- Other switch configurations available
- Hygienic and corrosion resistant
- Tested to IEC 60947-3



PRODUCT DESCRIPTION

Switch Disconnectors housed in high-quality stainless steel enclosures.
 All stainless steel enclosures are IP66 rated at a minimum for robust protection against dust and water.
 Available in both black/grey and yellow/red.

Stainless steel is ideal for applications where hygiene and good protection against corrosion are important.
 These enclosures are also available with EMC and EMC/EX protection upon request.

Tested to IEC 60947-3.

Note! AI-cables cannot be connected directly to switch terminals. For AI-cable connection please use a bi-metal cable connector.

TECHNICAL DATA

GENERAL DATA

Weight	1,2 kg
Rated thermal current, I _{th}	25 A
Nominal values with cable size	4
Number of poles	3
Rated insulation voltage U _i	800 V
Enclosure dimensions	160x120x77mm
Terminals / Bolt size Cu	1.5-16

RATED OPERATIONAL CURRENT, I_E

Operational current - AC-21A - 500V	25 A
Operational current - AC-23A - 500V	16 A

Operational current - AC-22A - 690V	16 A
Operational current - AC-21A - 690V	25 A
Operational current - AC-21A - 400/415V	25 A
Operational current - AC-23A - 690V	16 A
Operational current - AC-22A - 500V	16 A
Operational current - AC-23A - 400/415V	16 A
Operational current - AC-22A - 400/415V	16 A

RATED OPERATIONAL POWER FOR 3-PHASE (1500 R.P.M.) SQUIRREL CAGE INDUCTION MOTORS (KW)

Operational power - AC-23A - 400/415V	7,5 kW
Operational power - AC-23A - 500V	7,5 kW
Operational power - AC-23A - 690V	11 kW

RATED FUSED SHORT CIRCUIT CURRENT

Peak value	3,8 kA
Back-up fuse	25 A
Rated short circuit making capacity at 690V, Icm	1 kA
Rated short time withstand current at 690V (1 s), Icw	0.7 kA
R.M.S value, IK	50 kA
Rated impulse withstand voltage Uimp	8 kV

RATED BREAKING CAPACITY, ICN

Breaking capacity - AC-23A - 400/415V	128 A
Breaking capacity - AC-23A - 500V	128 A
Breaking capacity - AC-23A - 690V	128 A

ADDITIONAL DETAILS

Country of origin	FI
Tariff code	85365080
Max terminal torque	1.8 Nm
Electrical endurance	3000 operations
Mechanical endurance	50000 operations
Switch colour	Black/grey

