

## ECO MULTIFUNCTION TIMER

MFR

16373.2

MFR-7 MF TIMER 24-240VAC/DC 5A, 1PCO Eco

- 17.5mm wide
- Time Range 0.05 sec - 10 Hours
- 7 functions
- 24...48vdc,/24...240vac Supply
- 1 x 5A change-over contact

### PRODUCT DESCRIPTION

### TECHNICAL DATA

<b>Basic accuracy</b>	<1,5%(of the range)
<b>Colour</b>	Light gray
<b>Connection type</b>	Screw
<b>Contact material</b>	AgNi
<b>Continuous current max / Inrush current max</b>	5 / 5 A
<b>Control contact terminals</b>	A1-B1
<b>Country of origin</b>	AT
<b>Cross section single wire from</b>	2,5 mm <sup>2</sup>
<b>Cross section single wire to</b>	0,25 mm <sup>2</sup>
<b>Cross section stranded with ferrule from</b>	0,25 mm <sup>2</sup>
<b>Cross section stranded with ferrule to</b>	1,5 mm <sup>2</sup>
<b>Electrical life in hours (AC1)</b>	1x10 <sup>5</sup>
<b>Fuse</b>	5 A
<b>Height TS 35 / 7.5 with base</b>	57,9 mm
<b>Length</b>	90 mm
<b>Mechanical life hours</b>	1x10 <sup>6</sup>
<b>Nominal frequency min</b>	48 Hz
<b>Number of functions</b>	6
<b>Pack size</b>	10
<b>Rated contact voltage</b>	250V ac

<b>Rated frequency max</b>	63 Hz
<b>Relay contact</b>	1 CO
<b>Repeatability accuracy</b>	<0,5% / $\pm$ 5 ms
<b>Setting accuracy</b>	<5% (of the range)
<b>Stripping length</b>	7 mm
<b>Supply voltage</b>	24...240 ac, 24...48 ac/dc
<b>Switching voltage max</b>	250 v ac
<b>Tariff code</b>	85364900
<b>Temperature influence</b>	<0,05% / °C
<b>Time range</b>	50 ms - 10 h
<b>Tolerance</b>	-15% / 10%
<b>Torque</b>	0,5 Nm
<b>Weight</b>	42,3 g
<b>Width</b>	17,5 mm

