

ECO MULTIFUNCTION TIMER

MFR



16373.2

MFR-7 MF TIMER 24-240VAC/DC 5A, 1PCO Eco

- 17.5mm wide
- Time Range 0.05 sec - 10 Hours
- 7 functions
- 24...48vdc,/24...240vac Supply
- 1 x 5A change-over contact

PRODUCT DESCRIPTION

TECHNICAL DATA

Basic accuracy	<1,5%(of the range)
Colour	Light gray
Connection type	Screw
Contact material	AgNi
Continuous current max / Inrush current max	5 / 5 A
Control contact terminals	A1-B1
Country of origin	AT
Cross section single wire from	2,5 mm ²
Cross section single wire to	0,25 mm ²
Cross section stranded with ferrule from	0,25 mm ²
Cross section stranded with ferrule to	1,5 mm ²
Electrical life in hours (AC1)	1x10 ⁵
Fuse	5 A
Height TS 35 / 7.5 with base	57,9 mm
Length	90 mm
Mechanical life hours	1x10 ⁶
Nominal frequency min	48 Hz
Number of functions	6
Pack size	10
Rated contact voltage	250V ac

Rated frequency max	63 Hz
Relay contact	1 CO
Repeatability accuracy	<0,5% / \pm 5 ms
Setting accuracy	<5% (of the range)
Stripping length	7 mm
Supply voltage	24...240 ac, 24...48 ac/dc
Switching voltage max	250 v ac
Tariff code	85364900
Temperature influence	<0,05% / °C
Time range	50 ms - 10 h
Tolerance	-15% / 10%
Torque	0,5 Nm
Weight	42,3 g
Width	17,5 mm

