


CROUZET GN0 SERIES SOLID STATE RELAY

Panel mount - AC output Three phase

GN025DSRL

- Zero cross switching
- Output current - 25 or 50 amps
- Built-in overvoltage protection
- LED status indicator forward and reverse



PRODUCT DESCRIPTION

TECHNICAL DATA

OVERVIEW

Output current	25 A
Output voltage	24-510V ac
Control voltage	12-30V dc
Mounting	Panel mount
Type of control	Special zero voltage turn on

OUTPUT SPECIFICATION

Output voltage	24-510V ac
Transient Voltage	1600 V pk
Maximum off-state leakage current	1 mA rms
1 Second surge current	230
Maximum 1 cycle surge current	320/_ (min) 420 (typ)
Maximum on-state voltage drop	1.18V pk
Thermal resistance junction to case	0,4 °C/W
Maximum 1/2 Cycle I ² t for fusing (A ² sec)	512/880
Minimum heat sink for rated current @ 40 °C	7 °C/W

Number of poles	3
-----------------	---

INPUT SPECIFICATION

Control voltage	12-30V dc
-----------------	-----------

Minimum turn-on voltage	12V dc
-------------------------	--------

Must turn-off voltage	1V dc
-----------------------	-------

Input current min	15 mA
-------------------	-------

Input Current Max	28 mA
-------------------	-------

Maximum turn-on time (ms)	1/2 cycle
---------------------------	-----------

Maximum turn-off time (ms)	1/2 cycle
----------------------------	-----------

GENERAL SPECIFICATION

Dielectric strength input to output (50/60Hz)	4000 V rms
---	------------

Ambient operating temperature	-40 ... +80°C
-------------------------------	---------------

Ambient storage temperature	-40 ... +100°C
-----------------------------	----------------

Weight	200 g
--------	-------

Height	76,5 mm
--------	---------

Width	100 mm
-------	--------

Depth	34,7 mm
-------	---------

Housing material	UL94 V-0
------------------	----------

Material base	Aluminium
---------------	-----------

LED input status indicator	Green
----------------------------	-------

Approvals	CE, UKCA, cRUus
-----------	-----------------