

## SLO OUTPUT RELAY FOR A LOADS

SLO5TR

O/P Plug-in Relay 5V dc / 0-240V ac 3A

- DC control/ac load
- Galvanic isolation 4kV, 8mm creep distance
- Effective interference elimination
- Compatible with NPN and PNP logic
- LED indication



### PRODUCT DESCRIPTION

The relays are used as an interface between control systems and ac loads. The relays can handle inductive loads without load current reduction, which makes them very suitable for connection to, for example, solenoid valves and contactors. The relays have no mechanical parts, which means very reliable application. The integrated interference protection provides reliable operation even in very demanding electrical environments. Thanks to interference protection, signal cables can be run alongside power cables on, for example, cable racks for more than 1.5 km without capacitive cross-talk affecting relays. The SLOP models are especially designed for connection to 2-wire sensors that produce leakage current. The relays are blind to leakage currents up to 3.0 mA. For forward/reverse control of ac motors, the SLO24TRA is used. The relay has a higher operating voltage and withstands regenerated voltages from motors.

## TECHNICAL DATA

### INPUT DATA

Turn-off voltage	2,5 V
Input impedance, typ	0,3 kΩ
Release time	11 ms
Input current at nominal voltage, typ	15 mA
Response time	0,5 ms
Switching voltage	2,7 V
Input current at nominal voltage, max	17 mA
Input voltage nom	5

### OUTPUT DATA

Load current ac max	3 A
---------------------	-----

Peak current	90 A (20ms) A
Leakage current	1,5 mA
Load voltage ac max	265 V
Number of poles	1
Voltage drop	1 V

## GENERAL DATA

Storage temperature min	-40 °C
Material	PBT
Temperature operational max	70 °C
Weight	40 g
Width	12,5 mm
Storage temperature max	70 °C
Temperature operational min	-10 °C
Approvals	CE, UL



