

CKR48 SERIES

CKRD4820

DIN Rail SSR 22.5mm 530V ac 20A, 4.5-32V dc In, ZC



- Load Current 10, 20, 30 A
- Operating Voltage 48-530 VAC
- Control Voltage 4-32 VDC, 110-280 VAC, 90-140 VAC, 18-36 VAC
- Broad range of control voltage



PRODUCT DESCRIPTION

Ratings from 10A to 30A @ 530 VAC - Slim 22.5mm (width) package - SCR output for heavy industrial loads - LED input status indicator - AC or DC control - zero voltage (resistive loads) or instantaneous turn on (inductive loads) output

- Rating from 10A to 30A @ 530VAC
- Slim 22.5mm (width) package
- SCR output for heavy industrial loads
- LED input status indicator
- AC or DC control
- Zero Voltage (resistive loads) or Instantaneous (inductive loads) turn-on output

TECHNICAL DATA

OVERVIEW

Type of control	Zero voltage turn on
Connection	Screw connection
Additional features	N/A
Output current	20 A
Control voltage	4-32V dc
Output voltage	48-530V ac

OUTPUT SPECIFICATION

Number of poles	1
-----------------	---

Output voltage 48-530V ac

INPUT SPECIFICATION

Control voltage 4-32V dc

GENERAL SPECIFICATION

Depth 99 mm

Storage temperature min -40 °C

Temperature operational max 80 °C

Weight 280 g

Width 22,5 mm

Storage temperature max 125 °C

Temperature operational min -40 °C

LED indication Input status indication

Height 81,9 mm

