

CKR24 SERIES

CKRD2410
 DIN Rail SSR 22.5mm 280V ac 10A, 4.5-32V ac In, ZC



- Load current 10, 20 and 30A
- Operating Voltage 24-280 VAC
- Control Voltage 4-32 VDC, 110-280 VAC, 90-140 VAC, 18-36 VAC
- Broad range of control voltage



PRODUCT DESCRIPTION

Ratings from 10A to 30A @ 280 VAC - Slim 22.5mm (width) package - SCR output for heavy industrial loads - LED input status indicator - AC or DC control - zero voltage (resistive loads) or instantaneous turn on (inductive loads) output.

- Rating from 10A to 30A @ 280VAC
- Slim 22.5mm (width) package
- SCR output for heavy industrial loads
- LED input status indicator
- AC or DC control
- Zero Voltage (resistive loads) or Instantaneous (inductive loads) turn-on output

TECHNICAL DATA

OVERVIEW

Type of control	Zero voltage turn on
Connection	Screw connection
Additional features	N/A
Output current	10 A
Control voltage	4-32V dc
Output voltage	24-280V ac

OUTPUT SPECIFICATION

Number of poles	1
Output voltage	24-280V ac

INPUT SPECIFICATION

Control voltage	4-32V dc
------------------------	----------

GENERAL SPECIFICATION

IP class	IP20
Depth	99 mm
Storage temperature min	-40 °C
Temperature operational max	80 °C
Weight	280 g
Width	22,5 mm
Storage temperature max	125 °C
Temperature operational min	-40 °C
LED indication	Input status indicator
Height	81,9 mm

