

MECHANICAL HYGROSTAT - KFR 012

KFR

01241.0-00

KFR 012 Hygrostat, Preset 50% RH, normally open

- Preset for humidity (65 % rF or 50 % rF)
- Compact
- High breaking capacity
- Simple mounting and quick installation



PRODUCT DESCRIPTION

This mechanical hygrostat KFR 012 is preset at 65 % or 50 %. This makes it easier to install hygrometers. It can often be difficult to know which humidity is to be set on the hygrostat. If the hygrostat is set at a value that is too low, the heating fan runs too frequently and thus produces large energy losses, or if the hygrostat is set at a value that is too high, components in the cabinet can be damaged. For the sake of simplicity, STEGO has developed two different models.

65 % humidity (rF) – for most cabinets with normal humidity

50 % humidity (rF) – for cabinets with components that are sensitive to high humidity.

TECHNICAL DATA

GENERAL DATA

Mounting	Clip on, DIN rail
Contact type	1 x N/O
Hysteresis humidity	4% RH
Control range humidity to	50 % RF
Colour	Light grey
Control range humidity from	50 % RF

RATED OPERATING CONDITIONS

Operational temperature	0 °C ... +60°C
Connection type	2-pole terminal for 2.5mm ²
Storage temperature	-20°C ... +80°C
Life span	> 50,000 cycles

Humidity storage	<90% RH
Contact resistance	<10 mΩ
Breaking capacity	250VAC, 5 (0.2) A

DIMENSIONS

Weight	0,04 kg
Depth	33 mm
Material of body	Plastic
Height	60 mm

SAFETY & APPROVALS

Flammability class	UL94-V0
IP class	IP20
Approvals	CE, UL, VDE

EMC	EN 55014-1-2, EN 61000-3-2, EN 61000-3-3
-----	--



