

DATALOGIC RIDA DBT6400

DBT6400-BK
DBT6400, BT Pocket 2D Area Imager, Black

- Detects 1D/2D code types
- Wide VGA 752 x 480 pixel image sensor
- 3,000+ reads per charge
- Interfaces: USB COM, USB-OEM, USB keyboard



PRODUCT DESCRIPTION

TECHNICAL DATA

1D Code types	Auto discriminates all standard 1D codes
2D Code Types	Aztec Code, China Han Xin Code, Data Matrix, MaxiCode, Micro QR Code, QR Code, Aztec Mesas
Approvals	RoHS
Battery	Lithium-ion 700 mAh
Charge time	2.5 hrs
Colour	Black
Dimension (mm)	112.5 x 42.3 x 27.5
Drop resistance	Withstands repeated drops from 5ft onto a concrete surface
Humidity	5-95% (Non-condensing)
Immunity to ambient light	0-100,000 lux
Interface	USB COM, USB-OEM, USB keyboard wedge
IP class	IP50
Kit	No
Light source	White
Postal Code Types	China Post, KIX Post, Planet Code, Postnet, Royal Mail Code (RM4SCC), UK Postal, Australia Postal, Japan Postal, Canadian Post, Korea Post

Readable code types	1D / Linear Codes, 2D Codes, Postal Codes, Stacked Codes
Reading angle window	Pitch: +/-65°; Tilt: up to 360°; Skew: +/-60°
Reads per charge	3000
Resolution	4 mil
Sensor Type	Wide VGA: 752 x 480 pixels
Stacked Code Types	EAN/JAN Composites, GS1 Databar Composites, GS1 Databar Expanded Stacked, GS1 Databar Stacked, GS1 Databar Stacked Omnidirectional, Macro PDF, Micro PDF 417, PDF 417, UPC A/E Composites
Storage temperature max	70 °C
Storage temperature min	-20 °C
Temperature operational max	50 °C
Temperature operational min	0 °C
Weight	85 g
Wireless	Yes
Wireless technology	Bluetooth Wireless Technology