

ENCLOSURE LIGHTING - SL 025

SL 025

02527.0-00

SL 025 Lamp with switch, 230V ac

- ** SOME ITEMS OUT GOING RANGE **
- ** SEE OBSOLETE LIST IN DOWNLOADS **
- Integrated outlet
- Low energy fluorescent lamp



PRODUCT DESCRIPTION

The Slimline is designed to take as little vertical space as possible and thus be concealed behind the cabinet's upper front edge. The risk for glare is thus minimal despite the 11 W low energy lamp providing as much light as a 75 W light bulb. Slimline has an integrated outlet for, for example, a soldering iron or other device, and as standard has a screw-mounted push button switch. Both a magnetic bracket and IR sensor are available as options. If a magnetic bracket is chosen, installation is very simple and the lamp can be easily moved around in the cabinet to suit each situation. If you would also prefer an IR sensor, it only reacts when the door is opened, even if the door is transparent. Installation is facilitated even more in that a door switch is unnecessary.

TECHNICAL DATA

GENERAL DATA

Mounting	Screw fixing
Nominal voltage	230 V AC
Activation	Switch
Connection type	3-pole terminal
Light source	Low energy Fluorescent lamp
Luminance	900Lm
Life span	10,000 Hrs

DIMENSIONS

Length	345 mm
Width	345 mm
Height	40 mm

ELECTRICAL SPECIFICATION

Frequency	50/60 Hz
-----------	----------

SAFETY & APPROVALS

IP class	IP20
----------	------

Approvals	CE, EAC, GS, RoHS, UL, UL E234324, VDE
-----------	--

Flammability class	UL94-V0
--------------------	---------

MATERIALS - CONDITIONS

Material plastic housing	Plastic
--------------------------	---------

Colour	Light grey
--------	------------

Operational temperature	-20°C ... +50°C
-------------------------	-----------------

Storage temperature	-45°C ... +70°C
---------------------	-----------------

Operating humidity	< 90% RH
--------------------	----------

Humidity storage	<90% RH
------------------	---------

ADDITIONAL DATA

Weight	0,4 kg
--------	--------

Voltage max	230 V ac
-------------	----------

Voltage min	230 V ac
-------------	----------

