

ENCLOSURE LIGHTING - KL 025

KL 025

02505.9-01

KL 025 Lamp, 120V ac, 60Hz, without socket, magnetic
- OBSOLETE

- ** OBSOLETE ** END OF LIFE 31/12/20
- Replaced by LED 121/122



PRODUCT DESCRIPTION

The KL025 cabinet light is compactly designed especially for use in the cabinet. With the powerful magnetic mount, the lighting can easily be installed without any installation work anywhere in steel cabinet. Alternatively, it can be screw-mounted with 2 pieces of DIN (150-180 mm long) pieces inserted from the short sides. The integrated socket enables operation of other electrical auxiliary equipment.

Other voltages may be on request.

TECHNICAL DATA

GENERAL DATA

| | |
|-----------------|------------------|
| Mounting | Magnetic mount |
| Luminance | 900Lm |
| Nominal voltage | 120 V AC |
| Connection type | 3-pole terminal |
| Life span | 5,000 hrs |
| Activation | Switch |
| Light source | Fluorescent lamp |

DIMENSIONS

| | |
|--------|--------|
| Length | 355 mm |
| Width | 355 mm |
| Height | 70 mm |

ELECTRICAL SPECIFICATION

| | |
|-------------------|-------|
| Frequency | 60 Hz |
| Power consumption | 9 W |

SAFETY & APPROVALS

| | |
|-----------|-------------------|
| IP class | IP20 |
| Approvals | CE, EAC, GS, RoHS |

MATERIALS - CONDITIONS

| | |
|--------------------------|-----------------|
| Operational temperature | -20°C ... +50°C |
| Material plastic housing | Plastic |
| Colour | Light grey |
| Storage temperature | -45°C ... +70°C |
| Humidity storage | <90% RH |
| Operating humidity | < 90% RH |
| Voltage min | 120 V ac |
| Voltage max | 120 V ac |
| Weight | 1 kg |

