

0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

ENCLOSURE LIGHTING LED 025 ECOLINE

Ecoline

02542.1-11 LED 025 Eco, 24-48V dc, screw fixing

- LED long lifetime
- · Externally switched version
- Wide AC/DC voltage range
- · Quick connect spring terminals





PRODUCT DESCRIPTION

LED025 ECOLINE is a LED light from STEGO with quick connection through spring clamp.

LED025 ECOLINE can be used for all types of panel or cabinet installations, but is particularly good when space is limited due to its optimal size. The lighting has a very long life due to LED technology, which results in savings in service and maintenance.

LED025 ECOLINE is available in three different mounting options to suit different applications: Magnetic assembly, which can be mounted very quickly and can be moved around the cabinet if necessary. Screw mounting, for "traditional" mounting.

Clip assembly, which is a type of screw mounting, but where the lighting can be angled and also easily moved as needed.

LED025 ECOLINE has the same luminance as a 95W bulb, but consumes only 5 W.

LED025 ECOLINE is available with both 100-240 V AC and 90-110 V DC in one and the same unit, which makes it easy for both purchases and storage.

TECHNICAL DATA

GENERAL DATA

| Mounting | Screw fixing |
|---------------------|--------------------------------|
| Luminance | 400Lm at 120° |
| Nominal voltage | 24-48 V DC |
| Connection type | 2-pole dual cage clamp |
| Electrical lifetime | 60 000h at +20 °C:ssa (+68 °F) |
| Life span | 60,000h at +20°C |
| Activation | No switch |
| Light source | LED |
| DIMENSIONS | |
| Length | 351 mm |

| Width | 52 mm |
|--------------------------|---|
| Height | 34 mm |
| ELECTRICAL SPECIFICATION | |
| Power consumption | 5 W |
| SAFETY & APPROVALS | |
| IP class | IP20 |
| Protection class | II (double insulated) |
| Approvals | CE, cULus, EAC, RoHS, UL, UL E234324, VDE |
| MATERIALS - CONDITIONS | |
| Operational temperature | -30°C +60°C |
| Colour | Transparent |
| Storage temperature | -40°C +85°C |
| Humidity storage | <90% RH |
| Operating humidity | < 90% RH |
| Material of body | Plastic |
| Voltage min | 20 V dc |
| Voltage max | 60 V dc |
| Weight | 0,2 kg |

