

KES-E ECO FLEXIBLE PUSH-IN SQUARE CABLE ENTRY GROMMET

KES-E

28810.6
KES-E 12/24, Push fit cable entry, 12 cable, 1.5 - 2.5mm wall thickness



- For cable, pipe & hose diameters 1mm to 16.1mm
- IP54 Push in cable entry
- Halogen and Silicon free
- High density, up to 50 cables
- Ecolab approved

PRODUCT DESCRIPTION

The KES-E range from Contactclip offers a cost-effective solution for multiple cable, hose, pipe or tube entries in a confined space.

This system is ideal for applications where a high IP and strain relief is not required.

Designed for cables, tubes and pipes without connectors, the range offers between 12 and 50 entries with diameters of 1mm to 16.1mm.

The choice of two TPE frames can be quickly and easily mounted without the use of any tools into enclosures of 1.5mm to 2.5mm or 2.5mm to 4mm wall thickness enclosures.

In order to insert cables/tubes, the membrane (with marked centring point) must be pierced, now the cables can be easily guided through.

The TPE material ensures IP54 seal in a smooth hygienic design.

TECHNICAL DATA

GENERAL DATA

Installed height	5 mm
IP class	IP54
Colour	Grey
Number of cables	12
Length	142 mm
Mounting	Push in
Number of cables x cable diameter	12 x 1.0mm-15.0mm
Width	44 mm
Type	KES-E
Approvals	cUL, UL
NEMA class	12

MOUNTING DETAILS

Width of cutout	36 mm
Wall thickness	1.5mm-2.5mm
Length of cutout	112 mm

MATERIALS

Flammability class	V-0
Sealing material	TPE
Operating temperature from	-40 °C
Halogen-free	Yes
Material	TPE
Operating temperature to	90 °C
Silicone-free	Yes

APPROVALS

UL test standard	UL 508A
Approvals	cUL, UL
cUL test standard	CSA C22.2 No. 14-18

ADDITIONAL DATA

Pack size	10
Country of origin	DE
Tariff code	39259020
Weight	40,28 g

