

## KES-R-M ROUND LATCHING AND SCREW MOUNT CABLE ENTRY

### KES-R-M

28910.6

KES-R M25/3, M25 Snap in/Screw Push in cable entry, 3 cables, 3.2mm to 6.5mm mixed

- For cable, pipe & hose diameters 1.5mm to 22.2mm
- High density, up to 68 cables
- For wall thickness 1 to 11mm
- IP54- Snap in, IP66 - Screw Mount
- M25 to M63mm  $\varnothing$  hole sizes



### PRODUCT DESCRIPTION

The KES-R-M from Contactclip has an additional glass-fibre reinforced screw thread to achieve IP66 rating to and allows it to be fitted in to enclosures up to 11mm thick.

These can be retro-fitted in place of a conventional gland form M25 through to M63.

The TPE membrane is the same as the KES-E-R cable entry solution and is ideal for bringing in multiple cables, tubes and pipes where space is tight. These are quick and easy to fit on enclosures, they can be snapped in (IP54) or with an additional nut, IP66 can be achieved. This system is ideal for applications where there are multiple entries that need a higher IP and strain relief is not required. Available for panel thickness 1 to 11mm with configurations of up to 68 entries of 1mm to 22.2mm cable diameter.

## TECHNICAL DATA

### GENERAL DATA

Installed height	8 mm
IP class	IP54, IP66
Colour	Grey
Number of cables	3
Length	38 mm
Mounting	Push in, Screw fixing
Number of cables x cable diameter	1 x 3.2mm-6.5mm, 2 x 3.2mm-5.2mm
Width	38 mm
Type	KES-R-M
Approvals	cUL, UL

NEMA class	12, 4X
------------	--------

## MOUNTING DETAILS

Torque of the fixing screws	3 Nm
Wall thickness	1.0mm-2.5mm (snap-in), 1.0mm-11mm (screw)
Drillhole diameter	25 mm

## MATERIALS

Flammability class	V-0
Sealing material	TPE
Operating temperature from	-40 °C
Halogen-free	Yes
Material	Polyamide 6.6, TPE
Operating temperature to	90 °C
Silicone-free	Yes

## APPROVALS

UL test standard	UL 508A
Approvals	cUL, UL
cUL test standard	CSA C22.2 No.1-18

## ADDITIONAL DATA

Pack size	10
Country of origin	DE
Tariff code	39259020
Weight	13,61 g



