


INSULATED BOOTLACE FERRULES FOR DUAL CABLES

3003.0

HZL 0.5, 0.5 x 8mm, Dual Ferrule, Orange

- Funnel feed-in made of polypropylene
- Heat resistant up to 120 °C
- For wires from 0.5...150 mm²
- Material: E-Cu/A-Cu, galvanically tin-plated



PRODUCT DESCRIPTION

The special shape of the plastic collar makes it easy to feed in two wires in one wire-end ferrule.

TECHNICAL DATA

GENERAL DATA

| | |
|-----------------------------------|---------------------|
| Colour | Orange |
| Cross section max | 0,5 mm ² |
| Rated wire cross section to (AWG) | 20 |
| Standard | German Standard |

DIMENSIONS

| | |
|---------------------|---------|
| Length | 14 mm |
| Length of tube | 8 mm |
| Stripping length | 11 mm |
| Thickness of collar | 0,3 mm |
| Thickness of tube | 0,15 mm |
| Diameter of tube | 1,4 mm |

MATERIALS

| | |
|----------------|--------------|
| Conductor tube | Copper alloy |
|----------------|--------------|

| | |
|-----------------------------------|----------------------------|
| Contact surface | Galvanic tin-plated, shiny |
| Plastic collar | Polypropylene-homopolymer |
| Operating temperature from | -5 °C |
| Operating temperature to | 105 °C |

APPROVALS

| | |
|-------------------------|-----|
| DIN 46228-4:1990 | Yes |
| DIN 46228-1:1992 | No |

ADDITIONAL DATA

| | |
|--------------------------|----------|
| Tariff code | 85369010 |
| Country of origin | DE |
| Weight | 0,14 g |
| Pack size | 500 |

