

## INSULATED BOOTLACE FERRULES ON REEL 0.34MM<sup>2</sup> TO 2.5MM<sup>2</sup>

V30MA000312

0.34mm<sup>2</sup> x 6mm ferrule on Reel - Cyan

- Funnel feed-in made of polypropylene
- Heat resistant up to 120 °C
- Material: E-Cu/A-Cu, galvanically tin-plated
- Up to 5000 ferrules in a reel



### PRODUCT DESCRIPTION

### TECHNICAL DATA

#### GENERAL DATA

Colour	Turquoise
Cross section max	0,34 mm <sup>2</sup>
Rated wire cross section to (AWG)	22
Standard	German Standard

#### DIMENSIONS

Length	10 mm
Length of tube	6 mm
Stripping length	8 mm
Thickness of collar	0,25 mm
Thickness of tube	0,15 mm
Diameter of collar	2 mm
Diameter of tube	0,85 mm

#### MATERIALS

Conductor tube	Copper alloy
----------------	--------------

<b>Contact surface</b>	Galvanic tin-plated, shiny
<b>Plastic collar</b>	Polypropylene-homopolymer
<b>Operating temperature from</b>	-5 °C
<b>Operating temperature to</b>	105 °C

## APPROVALS

<b>DIN 46228-4:1990</b>	Yes
<b>DIN 46228-1:1992</b>	No

## ADDITIONAL DATA

<b>Tariff code</b>	85369010
<b>Country of origin</b>	DE
<b>Weight</b>	0,06 g
<b>Pack size</b>	5000