

TRI-RATED INSULATED FERRULES ON REEL 0.5MM² TO 1.5MM²

V30MA004933

0.5mm² x 8mm ferrule on Reel - Orange

- Made of durable tin-plated copper for reliability.
- Designed for easy installation in tight spaces.
- Heat resistant up to 120 °C
- Can be processed without a tool change
- Material: E-Cu/A-Cu, galvanically tin-plated



PRODUCT DESCRIPTION

TECHNICAL DATA

GENERAL DATA

Colour	Orange
Cross section max	0,5 mm ²
Rated wire cross section to (AWG)	20
Standard	German Standard

DIMENSIONS

Length	14 mm
Length of tube	8 mm
Stripping length	10 mm
Thickness of collar	0,25 mm
Thickness of tube	0,15 mm
Diameter of collar	2,9 mm
Diameter of tube	1,1 mm

MATERIALS

Conductor tube	Copper alloy
----------------	--------------

Contact surface	Galvanic tin-plated, shiny
Plastic collar	Polypropylene-homopolymer
Operating temperature from	-5 °C
Operating temperature to	105 °C

APPROVALS

DIN 46228-4:1990	Yes
DIN 46228-1:1992	No

ADDITIONAL DATA

Tariff code	85369010
Country of origin	EEC
Weight	0,09 g
Pack size	4000