


INSULATED BOOTLACE FERRULES 6MM² TO 150MM²

V30AE000025

6mm² x 12mm Ferrule - Black

- Funnel feed-in made of polypropylene
- Heat resistant up to 120 °C
- For wires from 6...150 mm²
- Material: E-Cu/A-Cu, galvanically tin-plated



PRODUCT DESCRIPTION

When the individual strands at the ends of finely stranded wires need to be protected and to provide a more robust connection, then our Z + F wire-end bootlace ferrules are an ideal solution.

The wire-end ferrules can be crimped easily and securely with Z + F crimping pliers or a variety of machines. The resulting connections function properly both electrically and mechanically.

European manufactured, this range ensures a reliable crimp without splitting.

TECHNICAL DATA

GENERAL DATA

Colour	Black
Cross section max	6 mm ²
Rated wire cross section to (AWG)	10
Standard	German Standard

DIMENSIONS

Length	20 mm
Length of tube	12 mm
Stripping length	14 mm
Thickness of collar	0,3 mm
Thickness of tube	0,2 mm
Diameter of collar	6,3 mm

Diameter of tube	3,5 mm
------------------	--------

MATERIALS

Conductor tube	Copper alloy
----------------	--------------

Contact surface	Galvanic tin-plated, shiny
-----------------	----------------------------

Plastic collar	Polypropylene-homopolymer
----------------	---------------------------

Operating temperature from	-5 °C
----------------------------	-------

Operating temperature to	105 °C
--------------------------	--------

APPROVALS

DIN 46228-4:1990	Yes
------------------	-----

DIN 46228-1:1992	No
------------------	----

ADDITIONAL DATA

Tariff code	85369010
-------------	----------

Country of origin	DE
-------------------	----

Weight	0,45 g
--------	--------

Pack size	100
-----------	-----