


## INSULATED BOOTLACE FERRULE FOR DUAL CABLES

V30AE006564

0.34mm<sup>2</sup> x 8mm Dual Ferrule - Cyan

- Funnel feed-in made of polypropylene
- Heat resistant up to 120 °C
- For wires from 0.5...16 mm<sup>2</sup>
- Material: E-Cu/A-Cu, galvanically tin-plated



### PRODUCT DESCRIPTION

### TECHNICAL DATA

#### GENERAL DATA

Colour	Cyan
Cross section max	0,34 mm <sup>2</sup>
Rated wire cross section to (AWG)	22
Standard	UL (DIN)/German Standard

#### DIMENSIONS

Length	15 mm
Length of tube	8 mm
Stripping length	11 mm
Thickness of collar	0,25 mm
Thickness of tube	0,15 mm
Diameter of tube	1,2 mm

#### MATERIALS

Conductor tube	Copper alloy
Contact surface	Galvanic tin-plated, shiny

Plastic collar	Polypropylene-homopolymer
Operating temperature from	-5 °C
Operating temperature to	105 °C

## APPROVALS

DIN 46228-4:1990	Yes
DIN 46228-1:1992	No

## ADDITIONAL DATA

Tariff code	85369010
Country of origin	DE
Weight	0,14 g
Pack size	500

